

## **Technical Data Sheet**

Article-No:

**xxxxx-00000** 

# **SET Camino "Rack"**

## POWER GENERATORS FOR EXTREME REQUIREMENTS



Fully enclosed military diesel power generators for permanent installation in vehicles and shelters.

Very flexible mounting system for extreme space constraints.

Rack version with or without tank

### **Technical data**

	Power kW	Power kVA	Voltage	Frequency Hz	Engine	Coolant E / G	Noise dB
Camino 10DSR	8	10	230/400	50	Kohler	water	56
Camino 12DSR	10	12.5	230/400	50	Kubota	water	56
Camino 15DSR	12.5	15	230/400	50	Kohler	water	56
Camino 20DSR	16	20	230/400	50	Kohler	water	56
Camino 25DSR	20	25	230/400	50	Mitsubishi	water	56



#### **Technical Data Sheet**

Article-No:

xxxxx-00000

## **SET Camino "Rack"**

## Standard equipment

- Super sound capsule; all filters at one maintenance side
- Asynchronous generator, short circuit proof, water-cooled and suitable for unbalanced load
- Cooled exhaust system in the enclosure
- Exhaust silencer with high attenuation
- Cooling unit with circulation pumps and 230V fans with speed controller
- Basic control panel with key switch
- Electronical engine management with battery charger and automatic shutdown when: oil pressure too low, high temperature, water loss
- Computer optimized arrangement of the anti-vibration shock mounts, 4g in all directions.
- 1x Socket 2P/24V VG96917, 1x Socket 16A 230V 2P, 1x CEE 400V 5-pin

### Safety devices

- 1x MCB 16 A (B) 1P
- 1x MCB 16-32 A (C) 3P
- 1x RCD 16-40/ 0,03A, 4P
- Extremely quiet operation 56 dB(A) @7m
- Colour RAL 6031 green bronze
- Operating condition -32 °C / + 50 °C
- Storage temperature -40 °C / + 70 °C
- EMC to VG95373 class3
- industry documentation

#### **Additional items**

- Fully electronic control panel with LCD Display and Auto Start System
- Starting temperature -40°C
- Insulation monitoring
- Any RAL colour possible
- EMC to Mil STD 461G





